

# USB 2.0 Panel-Mount cable, USB B female with 2 screws to USB Mini B male, 30cm

**Product number** CU-MBM-003  
**Length** 300mm



## Product description

USB 2.0 Panel-Mount cable for industrial applications: USB connector type B female (mountable with 2 screws, UNC 4-40) to USB plug Mini B male, UL cable material, double shielded, length: 30cm

## Key features

- USB 2.0 Panel-Mount Cable
- Connection 1: Screw-on USB 2.0 B socket (with 2 embedded UNC 4-40 nuts) - FEMALE
- Connection 2: USB 2.0 Mini B plug - MALE
- Length: approx. 30cm
- Screw type: UNC 4-40 (2 mounting screws included)
- Screw spacing: 30mm (see drawing)
- PREMIUM quality
- UL 2725 cable material from brand manufacturers e.g. E238846 CHINGLUNG
- Gold-plated contacts
- Cable material with double shielding (foil shield + braided shield)
- Shielded connectors
- Data: 28 AWG/1P (twisted pair), copper (CU)
- Power 5V: thicker with 24 AWG/2C, copper (CU)
- USB 2.0 compatible + backwards compatible with USB 1.1
- Suitable for 480 MBit/s (high speed), 12 MBit/s (full speed) and 1.5 MBit/s (low speed)
- Cable diameter approx. 5mm
- Colour: black
- Alternative product designations: rack mount, USB REAR
- Customs tariff no. for USB Panel-Mount cables: 85444290
- CE, WEEE, RoHS-compliant (Restriction of Hazardous Substances, environmental protection standard)

## More images



