USB 4.0 cable, 2x Type-C[™] male, 1x angled, 40 Gbps, 1x angled, 240 watts, 8K, TPE, 1m





Product description

Flexible USB 4.0 cable with TPE jacket, 2x Type-C[™] male, 40 Gbps, 240 watts, display resolution max. 8K@60 Hz, Thunderbolt[™] 3 compatible, 1m

Highlights

- Flexible cable material thanks to TPE (feels like rubber)
- TPE for ecological sustainability
- Ultra-high speed: data transmission up to 40 Gbps
- Power Delivery 3.1 fast charging up to max. 240 W
- Exceptionally high image resolution possible: 8K@60 Hz
- Thunderbolt™ 3 compatible

Details

- High-quality USB 4.0 cable with e-marker: power, data and image transmission
- Connector 1: USB 4.0 Type-C[™] plug (male)
- Connector 2: USB 4.0 Type-C[™] plug (male) angled 90°
- Specification: USB 4.0 Gen.3x2
- compatible with Thunderbolt 3
- backwards compatible with USB 3.2, 3.0 and USB 2.0
- supports resolutions up to Ultra HD 8K@60Hz (7680 x 4320 pixels)
- High-quality workmanship with twisted wire pairs
- Moulded plugs with long bend protection for more flexibility and a long service life
- Power Delivery 3.1 up to max. 240 W (48V / 5A)
- Copper cores: AWG 24/32
- Gold-plated contacts
- Colour: black
- Outer diameter approx. 5.2mm
- Operating temperature: 0°C to 45°C
- Storage temperature: -20°C to 70°C
- e.g. for connecting smartphones, monitors, external housings and docking stations
- CE, WEEE, RoHS compliant

TPE = environmental protection

TPE is a new material with high elasticity like rubber and high strength at the same time. It is an environmentally friendly and non-toxic material. It contains no plasticisers. Compared to PVC, which is used in most cables, TPE has better elasticity. We are endeavouring to use the energy-saving and environmentally friendly TPE to replace PVC in many areas. TPE stands for thermoplastic elastomer. PVC (polyvinyl chloride) is a chlorinated resin to which plasticisers are usually added during processing. Even though TPE is a plastic, it is 100% recyclable and biodegradable. Thermoplastic elastomers for ecological sustainability.

More images







www.partsdata.eu



PINOUT

A1,B1,A12,B12 A4,B4,A9,B9		81,A12,B12 GND 84,A9,B9 VBUS	
A5 B5 A6 A7 A2 A3 B11 B10 B2 B3 A11 A10 A8 B8	CC Dp1 SSTXp1 SSTXp1 SSTXp1 SSTXp2 SSTXp2 SSTXp2 SSTXp2 SSRXp2 SSRXp2 SBU1 SBU2	A5 CC B5 B5 B5 D1 A7 D11 B11 SSTXp1 A2 SSRXp1 A3 SSRXp1 A1 SSTXp2 A1 SSTXp2 B3 SSRXp2 B3 SSRXp2 B3 SSRVp2 B3 SSRVp2 B8 SBU2	
	SHELL-		





www.partsdata.eu