

USB 2.0 cable PREMIUM with ferrite core UL white 1m

Product number CU-FWE-10

Length 1000mm



Product description

USB 2.0 cable with UL cable material, 1m, PREMIUM: double shielded, 1 ferrite core, gold plated plugs, AWG28/24, high speed 480 Mbps, colour: white

Key features

- USB 2.0 cable with 1 ferrite core
- PREMIUM Quality
- gold-plated plugs and contacts
- ferrite core on the side of the A plug (approx. 5cm away)
- Ferrite core size: approx. 20,5mm x 15,5mm (round)
- AWG28/1P (data lines, twisted pair) + AWG24/2C (power lines)
- double shielded with foil and braid shield + drain wire
- Cable Specification: HI-SPEED USB Revision 2.0 SHIELDED E324703 UL AWM STYLE 2725 80°C 30V VW-1
- Wire colours, internal: white, green, red, black (according to USB standard)
- Cable diameter: approx. 4.4mm
- Connector assembly: A male to B male (USB 2.0)
- shielded connectors with molded strain relief
- USB 2.0 High Speed compatible and compatible to USB 1.1
- suitable for 480 MBit/s (high speed), 12 MBit/s (full speed) and 1.5 MBit/s (low speed)
- Colour: white with gold-plated plugs on the outside
- Customs tariff number for USB cable: 85444290

More images




A

PINOUT
USB 2.0 A/B cable

B

POWER	AWG 24	1		1	ROT RED
DATA	AWG 28	2		2	WEISS WHITE
DATA	AWG 28	3		3	GRÜN GREEN
POWER	AWG 24	4		4	SCHWARZ BLACK
SHELL			BRAID + DRAIN	SHELL	



= paarig verdreht | twisted pair

