7 Ports USB 3.2 Gen 1 Metal HUB with 1.5A Charging Power

Product number EX-1189HMVS-3



Product description

7 Ports USB 3.2 Gen 1 Metal HUB with 1.5A Charging Power for Smartphones and Tablets

Product information

The EX-1189HMVS-3 provides 7 USB 3.2 Gen 1 (previously called USB 3.0) screwable downstream ports with 15KV ESD surge protection for each output. In doing so, it simultaneously provides 1.5A power for up to 4 ports for charging iPhone, iPad, smartphone and tablet. The included EX-K1571V cable can be attached to the EX-1189HMVS-3 with thumbscrews without a screwdriver. It can be used in automation, industrial and office applications. Thanks to its special housing, the EX-1189HMVS-3 can be screwed to the wall, under a table or in a 19" cabinet (optional with EX-6099).

- USB 3.2 Gen 1 Metal HUB with 7 ports
- 15KV ESD Surge Protection for all 7 ports
- Power 12V/3A with DC-Jack or +7V to +24V with Terminal Block
- Power supply optionally also from the USB-BUS +5V (Bus-Power)
- Automatic recognition of the data transfer rate for the attached external devices
- Supports simultaneously 1.5A current on maximum 4 ports
- Support BC v1.2: SDP/CDP/DCP Charging Modes
- · Rugged metal housing
- 7x USB Operating Display
- 1x LED Power Display
- Internal jumper for individual control of power supply:
- - ENA = bus power operation possible
- - DIS = operation with power supply only (self power)

Packaging contents:

• EX-1189HMVS-3, USB 3.2 Gen 1 cable 1.5m, Power Supply 12V/3A, Manual

www.partsdata.de www.partsdata.eu www.partsdata.fr

More images







Category:	USB HUB
Interface:	USB 3.2 Gen 1
Number of ports:	7
Inputs:	USB-B socket
Outputs:	7x USB-A socket
Power connection:	DC Jack + TB 7-24V
Data transmission:	5Gbps
Mounting Type:	Desktop
Surge protection:	15KV ESD
Temperature range:	0°C to +55°C
Application:	Premium
Charging power total:	31.5 W
Cable length:	1.5m
Colour:	black
Housing:	Metal

