

USB 3.0 cable A to MICRO B with screws 3m

Product number BUM-S18-30

Length 3000mm



Product description

USB 3.0 Micro B cable, length 3m, plug USB 3.0 A to USB 3.0 Micro B with screws, screw spacing 18mm, screw type M2 x 0.4, AWG24/26, double shielded, Super-Speed-Modus (max. 5Gbps), black

Key features

- USB 3.0 Micro B cable with 2 screws
- for industrial cameras according to USB3 Vision Standard™
- USB 3.0 type A plug male to USB 3.0 type Micro B male with screws
- Screw type: M2 x 0.4 (standard)
- Screw distance: 18 mm according to USB3 Vision Standard™
- Never exceed a max. torque of 0.3 Nm when fastening the M2 screws.
- High end cable material e.g. from Space Shuttle (E101344) or from DER AN (E74020-C)
- 28 AWG data cable and 26 AWG power cable (CU)
- UL Cable material AWM STYLE 2725 80°C VW-1 Universal Serial Bus 3.0
- Cable diameter: approx. 5.5 mm
- Data transfer rate up to 5 Gb/s
- CE, WEEE, RoHS-compliant according to current EU environmental regulations
- e.g. for cameras from Point Grey (e.g. Grasshopper3), Baumer Optronic (e.g. VisiLine Serie with USB3 Vision interface, Modell VLU), Basler (e.g. ace USB 3.0 Camera), IDS Imaging Development Systems (e.g. USB3 uEye LE, uEye ML, uEye LE), Toshiba Teli (BU Serie), Sentech (STC-M Serie), Matrix Vision (e.g. USB3 Vision - mvBlueFOX3) or XIMEA.
- Customs tariff no. for USB 3.0 cables: 85444290
- Blue contact carrier according to USB 3.0 standard
- Colour: black

More images

