

Cat. 6A Rack Mount (Panel Mount) cable with 2 screws, 2m

Product number HX-NM-200

Length 2000mm



Product description

Cat. 6A Rack Mount (Panel Mount) cable with 2 screws, 2m

Technical data

- RJ45 panel mount cable / rear cable / mounting cable for Ethernet etc.
- for mounting on an enclosure with a corresponding cut-out or for slot brackets
- connector 1: RJ45 socket screw-on (8P8C female)
- screw spacing / hole spacing for mounting: 25mm
- connector 2: RJ45 plug (8P8C male) with latching nose protection
- gold-plated contacts for excellent, high-performance network connection
- specification: Cat. 6A, also suitable for Cat.6, Cat.5e or ISDN/DSL
- for 10 Gigabit Ethernet 10BASE-T, 100BASE-TX, 1000BASE-T, 10/100/1000/10000 Mbit/s
- shielding class S/FTP (PiMF, Pairs in Metal Foil), i.e. aluminium foil shielding for individual wire pairs
- also aluminium braided shielding for the cable jacket
- thick copper cores AWG 26 BC (7/0.16 mm)
- halogen-free cable material: LSZH LS0H (Low Smoke Zero Halogen)
- max. bandwidth 500 Mhz
- cable diameter: approx. 6.2mm
- colour: black
- colour coding/contacting: EIA/TIA 568B, assignment 1:1
- contact resistance: max. 5 ?
- insulation resistance: 10/20 M? @ 5-10/1-3 M
- impedance: 100 ?
- scope of delivery: 1 panel mount cable with 2 screws (pre-assembled, type M3).
- other designations: RJ45 Rack Mount, Panel Mount, Mounting Flange, Extension Cable, Mount Flange.
- CE, WEEE, RoHS compliant

More images



Cat. 6A

