USB 3.0 HUB with 4 ports metal body with over-current protection

Product number EX-1183HMVS-2



Product description

USB 3.0 HUB with 4 ports, metal body for industrial applications, with over-current protection, wall mount option, USB 3.0 cable and power supply 3A included, black

Product information

The rugged and industrial grade EX-1183HMVS-2 is a USB 3.2 Gen 1 metal hub for up to four end devices. The hub provides four screwable USB 3.2 Gen 1 downstream ports with 15KV ESD surge protection. It is possible to connect up to four external USB peripherals to one USB 3.2 Gen 1 port from notebook, desktop computer or server in 19" rack. It supports SuperSpeed USB 3.2 Gen 1 data transfer rate of up to 5Gbps and is backward compatible to USB 1.1. The included USB 3.2 Gen 1 cable can be attached to the EX-1183HMVS-2 with thumbscrews without a screwdriver. The EX-1183HMVS-2 can be powered via a DC jack, as well as a two wire terminal block connector (+7V to +48V). The HUB meets the special requirements of industrial applications.

- USB 3.2 Gen 1 Metal HUB with 4 Ports
- 15KV ESD Surge Protection for all 4 Ports
- Protection of Devices against voltage fluctuation
- Power +7V up to +48V DC over the DC-Connector or Terminal Block
- Power supply optionally also from the USB-Bus +5V (Bus-Power)
- · Easy installation with the optionally available DIN-Rail Kit
- Automatic recognition the data transfer rate for the attached external devices
- Supports 1,5A power for each output simultaneously
- Support BC v1.2: SDP/CDP/DCP Charging Modes
- Automatic detection of input polarity on the current terminal block
- Rugged Metal Case
- 1x LED Power-Indicator & 4x Status LED

Category:USB HUB

Interface:USB 3.2 Gen 1Connections: A socket

• Number of ports: 4

• Power connection: DC Jack + TB 7V-48V

• Design: esktop

• Surge protection: 15KV ESD

Housing: Metal
Colour: black
Cable_ screwable
Cable length meter: 1,5m
Application: Premium
Charging power total: 30 W

More images















