USB 3.0 HUB with 4 ports DIN RAIL version with metall body, EX-1185HMVS-2

Product number EX-1185HMVS-2



Product description

USB 3.0 HUB with 4 ports, DIN RAIL version, metall body for industrial applications, with 350W surge protection, USB 3.0 cable and DIN RAIL mounting kit included, EXSYS EX-1185HMVS-2

Product information

The rugged, industrial-grade EX-1185HMVS-2 USB hub with four USB 3.2 Gen1 (previously called USB 3.0) screwable outputs and 15KV ESD surge protection can be installed on the wall or on a carrier rail. It connects to a computer or server with the included USB 3.2 Gen1 cable. It supports Hi-Speed USB 3.2 Gen1 data transfer rate up to 5Gbit/s and is downward compatible to USB 1.1. It can be powered by USB bus power (7-48V) or via a two-wire terminal strip where the wires are just plugged in without screwdriver.

- USB 3.2 Gen1 Metal HUB with four Downstream ports
- 15KV ESD Surge Protection for all ports
- Power +7V up to +48V DC over the Terminal Block
- Power supply optionally also from the USB-BUS +5V (Bus-Power)
- Easy installation with the included DIN-Rail Kit
- · Compact industrial design
- Automatic recognition the data transfer rate for the attached external devices
- 900mA current on all 4 ports
- Automatic detection of input polarity on the current terminal block
- Rugged metal case
- LED Power Display
- Chip-Set: Genesys GL3523

Packaging Contents

EX-1163HM, USB 2.0 cable 2.0m, DIN-Rail Kit, Manual

www.partsdata.de www.partsdata.eu www.partsdata.fr

Category: USB HUBInterface: USB 3.2 Gen 1Connections: A socketNumber of ports: 4

• Power connection: TB +7V to +48V

• Design: Din-Rail

• Surge protection: 15KV ESD

Housing: Metal
Colour: black
Cable: screwable
Cable length meter: 1,5
Application: Industrial
Charging power total: 18 W

More images











