

USB 3.0 cable AB with screws on both sides, EXSYS EX-K1572V, 2m

Product number EX-K1572V

Length 2000mm



Product description

USB 3.0 cable AB with screws on both sides, 2m, EXSYS EX-K1572V, e.g. for EXSYS USB HUBs

Product information

- Connection cable USB 3.2 Gen 1 A male and B male with thumbscrews. The USB 3.2 Gen 1 connection cable provides a consistently high data transfer rate of up to 5Gbps thanks to the combination of a high-quality cable construction and connectors with copper contacts.
- The USB cable connects the computer that has a threaded A connector and the various EXSYS products that have threaded B connectors.

Technical specification

- USB 3.2 Gen 1 (USB 3.0) Connector Cable.
- Connectors: USB male A to USB male B screwable with thumbscrews.
- Hi-Speed, up to 5Gbit/s data transfer rate
- USB 3.2 Gen 1 standard, downward compatible to USB 2.0
- Cable material and contacts made of 99.9% oxygen-free copper (OFC)
- Cable diameter: 4.5 mm
- Conductor cross section: AWG28
- Space about knurled screw from the A-male connector its 19mm
- Space about knurled screw from the B-male connector its 24mm
- Shielding: braided and foil shielding
- Color: Black
- Length: 2.0m

More images



